



“Hızlı çözüm uygun fiyatın tek adresi”

Palmx XL-2024 Barkod Okuyucu

Genel

1D Çok Yönlü Lazer Barkod Okuyucu
24 Tarama Çizgisi
5 Mil Çözünürlük
Saniyede 1620 Tarama
0 ~ 250 mm okuma mesafesi

İşlemsel

Işık kaynağı 650 nm görülebilir lazer diyod (VLD)
Tarama çizgi sayısı 24 lazer çizgisi
Tarama Deseni 6 yönlü tarama deseni
Tarama Uzaklığı 0 ~ 250 mm (UPC/EAN 100%)
Tarama Hızı 1620 tarama/sn
Minimum Bar Genişliği 0.125 mm (5 mil) @ PCS 90%
Baskı Kontrastı 30% @UPC/EAN 100%
Göstergeler (LED) Mavi ve Kırmızı LED
Ses Tonu Programlanabilir beep tonu ve süresi
Sistem Arabirimleri Klavye, Seri (RS-232C), USB HID

Fiziksel

Yükseklik 152 mm
Derinlik 75 mm
Genişlik 152 mm
Ağırlık 576 gram
Kablo Standart 2 metre düz kablo

Elektriksel

Giriş Voltajı 9V DC
Çalışma Akımı 430 mA
EMC CE ve FCC DOC Uyumlu

Çevresel

Çalışma Sıcaklığı 0°C ~ 45°C
Muhafaza Sıcaklığı -20 °C ~ 60 °C
Nem 5% ~ 85% (Yoğunlaşmasız)
Işık Seviyesi Max 10.000 Lux
Darbe dayanıklılığı 1,5 metre

Desteklenen Barkod Tipleri

Standart UPC/EAN/JAN, UPC/EAN with Supplementary, JAN 8 & JAN 13, ISBN/ISSN, EAN, Code 39, Code 39 with full ASCII, Code 93, Code 128, Codabar (NM7), Trioptic Code 39, MSI/Plessey, GS1 Code, Interleaved 2 of 5, Addendum 2 of 5, IATA Code, China Postal Code, Code 32, Industrial 2 of 5, Standart 2 of 5, Discrete 2 of 5, Matrix 2 of 5, Code 11, UPC/EAN RSS, RSS Variants